

# **DATASHEET**

# **HL1100W Hughes LEO Terminal**

The Hughes HL1100W User Terminal (UT) includes a low-profile Electronically Steered Antenna (ESA) that represents the leading edge of Low Earth Orbit (LEO) antenna technology. The HL1100W ESA is a half-duplex, self-aligning terminal with a built-in modem. It has no moving parts and is optimized for operation over the OneWeb Ku-band LEO satellite constellation — providing access to affordable, fast, high bandwidth and low latency communications service. The HL1100W UT is ideal for a variety of applications for everyone, everywhere, all the time.

The HL1100W ESA is designed for the outdoor environment. It is lightweight, low-power, weather-tight and easy to install and maintain. It is constructed with a durable aluminum chassis and is configured to function right out of the box, self-pointing to the satellite constellation. The HL1100W UT is compact, easy to install and makes optimal use of the OneWeb system capabilities for low latency and high speeds.





The HL1100W User Terminal includes the following Indoor Unit (IDU).

 HL1100W-IDU: Wi-Fi 6 router with two GigE LAN ports, MoCA adapter for ethernet over coax and external power supply.

# **RF Specifications**

TX Frequency 14.0 GHz to 14.5 GHz RX Frequency 10.7 GHz to 12.7 GHz

Duplexity Half

#### Performance\*

Peak Downlink Data Rate 57 Mbps
Peak Uplink Data Rate 10 Mbps

EIRP +36.6 dBW (Dual Carrier)

G/T Up to 11.3 dB/K

### **Environmental and Mechanical Specifications**

Operating Temperature  $-40 \,^{\circ}\text{C}$  to  $+55 \,^{\circ}\text{C}$  (-40  $^{\circ}\text{F}$  to  $+131 \,^{\circ}\text{F}$ )

Outdoor Unit (ODU)

Dimensions 59.8 cm x 40.2 cm x 6.0 cm

 $(23.5 \text{ in.} \times 15.8 \text{ in.} \times 2.4 \text{ in.})$ 

ODU Weight 10.6 kg, (23.3 lbs.)
ODU Power 130W (typical)
Indoor Power Supply 100 V to 240 V AC

DC power options available

IFL Cable Length Up to 70 m, (231 ft) with

RG-6 coax

Agency Compliance: CE, R&TTE, FCC, Anatel, UKCA

Safety Compliance: UL, CE, IEC

## **Network Configuration**

Network OneWeb Satellite Constellation

Network features IP, differentiated QoS,

multi-APN

Wi-Fi Wi-Fi 6 (optional)

\*Performance subject to network configuration. Please consult your Eutelsat OneWeb contact for service offerings in your region.

